

SPECIFICATIONS			CASSETTE NON INVERTER	
			FDT71CR-S	FDT125CR-S
			FDC71CR-S	FDC125CR-S
Power Source			1Phase, 220/240V : 50Hz	3 Phase 380-415V, 50Hz
Cooling Capacity	kW		7.1	12.5
	BTU/h		24225	42650
Input	W		2290	4464
COP			3.1	2.8
EER			10.58	9.55
Max. running current		A	17	16.1
Inrush current		A	44	17
Sound power level	Indoor		64	68
	Outdoor		67	72
Sound pressure level	Indoor	dB(A)	Hi: 46 /Me: 35 /Lo: 33	Hi: 51 /Me: 43 /Lo: 41
	Outdoor		55	59
Air flow	Indoor	m3/min	Hi: 28 /Me: 21 /Lo: 19	Hi: 34 /Me: 30 /Lo: 23
	Outdoor		38	75
Exterior dimensions	Indoor	HxWxD mm	Unit : 246 x 840 x 840 Panel : 35 x 950 x 950	Unit : 298 x 840 x 840 Panel : 35 x 950 x 950
	Outdoor		640 x 850 (+65) x 290	845 X 970 X 370
Net weight	Indoor	kg	29.5 (Unit: 24 Standard Panel: 5.5)	32.5 (Unit: 27 Standard Panel: 5.5)
	Outdoor		47	87
Refrigerant			R410A	
Ref.piping size	Liquid/Gas	Ømm	6.35 (1/4")/15.88 (5/8")	9.52 (3/8") / 15.88 (5/8")
Refrigerant line (one way) length		m	Max. 30	Max. 50
Vertical height diff./Outdoor is higher/lower		m	Max.10/Max.10	Max.30/Max.15
Panel			T-PSN-3BW-E (Wireless) / T-PSA-3BW-E	
Remote control	Wireless		Standard (include T-PSN-3BW-E)	
	Wired		RC-EX1A, RC-E5, RCH-E3 (option) (need SC-BIKN option)	