

SPECIFICATIONS			CEILING SUSPENDED NON INVERTER	
			FDE71CRS-S1	FDE125CR-S
			FDC71CRS-S1	FDC125CR-S
Power Source			1Phase, 220/240V : 50Hz	3 Phase 380-415V, 50Hz
Cooling Capacity	kW		7.1	12.5
	BTU/h		24,225	42,650
Input	W		2,000	4,425
COP			3.55	2.82
EER			12.11	9.64
Max. running current		A	17	14
Inrush current		A	20	14
Sound power level	Indoor		63	64
	Outdoor		67	72
Sound pressure level	Indoor	dB(A)	Hi: 50 /Me: 39 /Lo: 36	Hi: 48 /Me: 46 /Lo: 38
	Outdoor		55	59
Air flow	Indoor	m3/min	Hi: 23 /Me: 16 /Lo: 13	Hi: 33 /Me: 29 /Lo: 18
	Outdoor		60	75
Exterior dimensions	Indoor	HxWxD	210 x 1320 x 690	250 x 1620 x 690
	Outdoor	mm	750 x 880 (+88) x 340	845 x 970 x 370
Net weight	Indoor	kg	32	42
	Outdoor		52	87
Refrigerant			R410A	
Ref.piping size	Liquid/Gas	Ømm	6.35 (1/4") / 15.88 (5/8")	9.52 (3/8") / 15.88 (5/8")
Refrigerant line (one way) length		m	Max. 30	Max. 50
Vertical height diff./Outdoor is higher/lower		m	Max.10/Max.10	Max.30/Max.15
Remote control	Wireless		Standard	
	Wired		RC-EX1A, RC-E5, RCH-E3 (option) (need SC-BIKN option)	