

CONSTANT SPEED SINGLE SPLIT DELUXE (COOLING) CR/CRR / CT/CTR SERIES




SRK09CRR-S
SRK12CR-S

NEW



SRK09CTR-S
SRK12CT-S

REFRIGERANT PIPE LENGTH



SRK09CRR-S
SRK12CR-S
SRK09CTR-S
SRK12CT-S



SRC09CRR-S/CTR-S

SRC12CR-S/CT-S

FUNCTIONS

ENERGY SAVING



AIR FLOW



CLEAN OPERATION & FILTER



COMFORT & CONVENIENCE



OTHERS



SPECIFICATIONS

MODEL		CRR/CTR / CR/CT SERIES					
		INDOOR UNIT		SRK09CRR-S	SRK09CTR-S	SRK12CR-S	SRK12CT-S
ITEM	OUTDOOR UNIT		SRC09CRR-S	SRC09CTR-S	SRC12CR-S	SRC12CT-S	
Power source			1 Phase, 220 / 230V, 50Hz	1 Phase, 220 / 230V, 50Hz	1 Phase, 220 / 230V, 50Hz	1 Phase, 220 / 230V, 50Hz	
Capacity	Cooling	kW	2.64	2.64	3.45	3.45	
		BTU/h	9,000	9,000	11,771	11,771	
	Heating	kW	--	--	--	--	
		BTU/h	--	--	--	--	
Input	Cooling	kW	0.868	0.868	1.120	1.120	
	Heating	kW	--	--	--	--	
EER	Cooling	BTU/hW	10.37	10.37	10.51	10.51	
	Heating	BTU/hW	--	--	--	--	
COP	Cooling	W/W	3.04	3.04	3.08	3.08	
	Heating	W/W	--	--	--	--	
Current	Cooling	A	4.0 / 3.8	4.0 / 3.8	5.3 / 5.1	5.3 / 5.1	
	Heating	A	--	--	--	--	
Exterior dimensions (H x W x D)	Indoor unit	mm	262 x 769 x 210	262 x 769 x 230	262 x 769 x 210	262 x 769 x 230	
	outdoor unit	mm	435 x 645 (+50) x 275	435 x 645 (+50) x 275	595x780 (+62) x 290	595x780 (+62) x 290	
Net weight	Indoor	kg	7.0	7.5	7.0	7.5	
	outdoor	kg	24.5	24.5	31.0	31.0	
Air Flow (Cooling)	Indoor unit	m ³ /min	10.2	10.5	10.2	10.5	
	outdoor unit	m ³ /min	23	23	32.0	32	
Compressor Motor			0.795	0.795	1.096	1.096	
Refrigerant			R410A	R410A	R410A	R410A	
Refrigerant Control			Capillary tubes	Capillary tubes	Capillary tubes	Capillary tubes	
Refrigerant piping	Liquid line	mm	6.35	6.35	6.35	6.35	
	Gas line	mm	9.52	9.52	12.7	12.7	
Connecting wiring	Power cord (Size x Core number)		1.5 mm ² x 3 cores (Including earth cable)	1.5 mm ² x 3 cores (Including earth cable)	1.5 mm ² x 3 cores (Including earth cable)	1.5 mm ² x 3 cores (Including earth cable)	
	Out-In Interconnect (Size x Core no)		1.5 mm ² x 3 cores (Including earth cable)	1.5 mm ² x 3 cores (Including earth cable)	1.5 mm ² x 3 cores (Including earth cable)	1.5 mm ² x 3 cores (Including earth cable)	
Connect method			Terminal Block (Screw fixing type)	Terminal Block (Screw fixing type)	Terminal Block (Screw fixing type)	Terminal Block (Screw fixing type)	