

SPECIFICATIONS			FLOOR STANDING NON INVERTER	
Indoor unit			FDF71CRS-S1	FDF125CR-S
Outdoor unit			FDC71CRS-S1	FDC125CR-S
Power Source			1Phase, 220/240V : 50Hz	3 Phase 380-415V, 50Hz
Cooling Capacity	kW		7.1	12.5
	BTU/h		24,225	42,650
Input	W		2,507	4,781
COP			2.83	2.61
EER			9.66	8.92
Max. running current	A		13.2	9.92
Inrush current	A		18	14.3
Sound power level	Indoor		58	63
	Outdoor		67	72
Sound pressure level	Indoor	dB(A)	Hi: 46 /Me: 38	Hi: 51 /Me: 44 /Lo: 43
	Outdoor		55	59
Air flow	Indoor	m3/min	Hi: 21 /Me: 15	Hi: 25 /Me: 17 /Lo: 15
	Outdoor		38	75
Refrigerant control			Capillary	Electronic Expansion Valve
Exterior dimensions	Indoor	HxWxD	1,850 x 600 x 320	1,850 x 600 x 320
	Outdoor	mm	640 x 850(+65) x 290	845 x 970 x 370
Net weight	Indoor	kg	49	52
	Outdoor		47	87
Refrigerant			R410A 1,450g	R410A 2,250g
Ref.piping size	Liquid/Gas	Ømm	6.35 (1/4") / 15.88 (5/8")	9.52 (3/8") / 15.88 (5/8")
Refrigerant line (one way) length			Max. 30	Max. 50
Vertical height diff./Outdoor is higher/lower			Max.10/Max.10	Max.30/Max.15
Remote control	Wireless		No Option	
	Wired		Standard	